(11) **EP 1 094 144 B1**(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention
of the grant of the patent:
17.12.2003 Bulletin 2003/51

(51) Int Cl.7: **D06F 37/30, H02K 1/27,**
H02K 1/30

(21) Application number: **00122734.7**

(22) Date of filing: **18.10.2000**

(54) **Structure of driving unit in drum type washing machine**

Aufbau der Antriebseinheit in einer Trommelwaschmaschine

Structure de l'unité d'entraînement dans une machine à laver à tambour

(84) Designated Contracting States:
DE ES FR GB IT

(72) Inventor: **Kim, Kwang Soo**
Changwon-shi, Kyongsangnam-do (KR)

(30) Priority: **19.10.1999 KR 9945319**
19.10.1999 KR 9945320
19.10.1999 KR 9945321
19.10.1999 KR 9945323

(74) Representative: **Geyer, Werner, Dr.-Ing. et al**
Patentanwälte
Geyer, Fehners & Partner
Perhamerstrasse 31
80687 München (DE)

(43) Date of publication of application:
25.04.2001 Bulletin 2001/17

(56) References cited:

(73) Proprietor: **LG ELECTRONICS INC.**
Seoul (KR)

EP-A- 0 620 308	EP-A- 1 094 145
DE-A- 4 335 966	US-A- 4 623 812
US-A- 5 528 092	US-A- 5 862 686

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 1 094 144 B1

1

EP 1 094 144 B1

2

Description**BACKGROUND OF THE INVENTION**Field of the Invention

[0001] The present invention relates to a drum type washing machine, comprising a tub for storing washing water, a drum of a metal rotatably mounted inside of the tub disposed horizontal to the ground, or with an angle to the ground for accommodating laundry therein, a shaft connected to the drum mounted inside of the tub through the tub for transmission of a driving force of the motor to the drum, bearings fitted onto outer circumferences of both end portions of the shaft for supporting the shaft, a bearing housing having stator fastening bosses at fixed intervals along a circumference of a central portion thereof for supporting the bearings, a stator having a plurality of magnetic cores each formed by stacking magnetic laminations each having a salient pole projected outward in a radial direction and a rib projected inward in a radial direction, both of which are formed as one unit, frames of insulating material for covering top and bottom surfaces of a magnetic core assembly of the magnetic cores, and coils each wound around each of the salient poles of the magnetic cores, a cup formed rotor having a rotor body of magnetic material with a side wall serving as a back yoke, that forms a magnetic flux path, and a rear wall formed as a unit with the sidewall, and permanent magnets fitted to the sidewall, and a connector connecting the rotor and the shaft.

Background of the Invention

[0002] In general, a drum type washing, making washing by using friction between a drum rotated by a motor and laundry in a state detergent, washing water, and the laundry are introduced into the drum, provides effects of beating and rubbing washing, but gives almost no damage to the laundry, and shows no entangling of the laundry. A structure of a related art drum washing machine will be explained with reference to FIG. 1. FIG 1 illustrates a longitudinal section of a related art drum type washing machine, provided with a tub 2 mounted inside of a cabinet 1, a drum 3 rotatably mounted on a central portion of inside of the tub 2. There is a motor 5a under the tub 2 connected with a pulley 18 and a drum shaft connected to a rear of the drum 3, to which a drum pulley 19 is coupled. And, the drum pulley 19 on the drum shaft and the motor pulley 18 connected to the motor 5a are connected by a belt 20 for transmission of power. And, there is a door 21 in a front part of the cabinet 1, with a gasket 22 between the door 21 and the tub 2. There is a hanging spring between an inside of an upper portion of the cabinet 1 and an outside of an upper portion of the tub 2, and a friction damper 24 between an inside of a lower portion of the cabinet 1 and a lower

side of an outside of the tub 2 for damping vibration of the tub 2 generated during spinning.

[0003] However, the related art washing machine has the following disadvantages since driving power of the motor 5a is transmitted to the drum 3 through the motor pulley 18, and the drum pulley 19, and the belt 20 connecting the motor pulley 18 and the drum pulley 19.

[0004] First, there is a loss of energy in a course of driving power transmission because the driving power is transmitted from the motor 5a to the drum 3, not directly, but through the belt 20 wound around the motor pulley 18 and the drum pulley 19.

[0005] And, the driving power transmission from the motor 5a to the drum 3, not directly, but through many components, such as the belt 20, the motor pulley 18, and the drum pulley 19, causes much noise in the course of power transmission.

[0006] The lots of components required for transmission of driving power from the motor 5a to the drum 3, such as the motor pulley 18, the drum pulley 19 and the belt 20, require many assembly man-hours. And, the more the number of components required for transmission of driving power from the motor 5a to the drum 3, the more number of spots which require repair, and the more frequent at which repair is required. The imbalance caused by the motor mounted to a lower part of rear of the tub 2 causes heavy vibration when the motor is rotated. Consequently, there is a weight balancer of metal or cement separately provided to an opposite position of the motor for system balancing.

[0007] In summary, the indirect driving power transmission from the motor 5a to the drum 3 through the motor pulley, the drum pulley, and the belt requires many repair, has much noise, waste of energy, and results in a deterioration of a washing capability.

[0008] DE-A-43 35 966 discloses a drum type washing machine comprising a stator with a plurality of magnetic cores and a cup formed rotor, as described at the beginning of the specification.

SUMMARY OF THE INVENTION

[0009] Accordingly, the present invention is directed to a drum type washing machine that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

[0010] An object of the present invention is to provide a drum type washing machine, in which the motor is coupled to the drum directly for reducing vibration, and either reducing a weight of the weight balancer or remove the weight balancer completely.

[0011] Another object of the present invention is to provide a drum type washing machine, which can reduce waste of energy by employing a BLDC motor that has a good energy efficiency.

[0012] Another object of the present invention is to provide a structure of a drum type washing machine, which involves no deformation of the rotor even if the

3

EP 1 094 144 B1

4

rotor rotates at a high speed, and which prevents overheating of the motor.

[0013] A further object of the present invention is to provide a drum type washing machine, which permits an easy assembly thereof.

[0014] Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

[0015] To achieve these and other advantages and in accordance with the purpose of the present invention, there is provided a drum type washing machine which includes a tub for storing washing water, a drum of a metal rotatably mounted inside of the tub disposed horizontal to the ground, or with an angle to the ground for accommodating laundry therein, a shaft connected to the drum mounted inside of the tub through the tub for transmission of a driving force of the motor to the drum, bearings fitted onto outer circumferences of both end portions of the shaft for supporting the shaft, a bearing housing having stator fastening bosses at fixed intervals along a circumference of a central portion thereof for supporting the bearings, a stator having a plurality of magnetic cores each formed by stacking magnetic laminations each having a salient pole projected outward in a radial direction and a rib projected inward in a radial direction, both of which are formed as one unit, frames of insulating material for covering top and bottom surfaces of a magnetic core assembly of the magnetic cores, and coils each wound around each of the salient poles of the magnetic cores, a cup formed rotor having a rotor body of magnetic material, e. g. of iron or iron alloy, with a sidewall serving as a back yoke that forms a magnetic flux path and a rear wall formed as a unit with the sidewall, and permanent magnets fitted to a setting surface of an "L" formed bent portion of the sidewall, a connector connecting the rotor and the shaft, and the rotor including cooling fins each formed by cutting the rear wall in a "C" form, and folding in a stator direction for cooling the stator, and the rotor further including openings each formed by the cutting of the rear wall and acting as vent holes for flow of air.

Advantageous embodiments of the invention are set forth in the subclaims.

[0016] It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of the

specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention:

[0018] In the drawings:

FIG. 1 illustrates a longitudinal section of a related art drum type washing machine;

FIG. 2A illustrates a longitudinal section of a drum type washing machine in accordance with a first preferred embodiment of the present invention;

FIG. 2B illustrates a detailed enlarged view of "A" part in FIG. 2A;

FIG. 2C illustrates a detailed enlarged view of "B" part in FIG. 2B;

FIG. 3 illustrates a right side view of FIG. 2B having a motor removed therefrom;

FIG. 4 illustrates a perspective view showing the rotor in FIGS. 2A~ 2C with a partial cut away view;

FIG. 5 illustrates an enlarged perspective view of "C" part in FIG. 4;

FIG. 6 illustrates a perspective view of a bottom of FIG. 4;

FIG. 7 illustrates a perspective view of the stator in FIG. 2;

FIG. 8 illustrates a perspective view of the connector in FIG. 2;

FIG. 9 illustrates a perspective view of a bottom of FIG. 8;

FIG. 10 illustrates a longitudinal section of key parts of a structure of a driving unit in a drum type washing machine in accordance with a second preferred embodiment of the present invention;

FIG. 11 illustrates a right side view of FIG. 10 having a motor removed therefrom;

FIG. 12 illustrates a longitudinal section of key parts of a structure of a driving unit in a drum type washing machine in accordance with a third preferred embodiment of the present invention; and,

FIG. 13 illustrates a longitudinal section of key parts of a structure of a driving unit in a drum type washing machine in accordance with a second preferred embodiment of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0019] Reference will now be made in detail to preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings. A drum type washing machine in accordance with a first preferred embodiment of the present invention will be explained with reference to FIGS. 2A ~ 9.

[0020] Referring to FIG. 2A, the drum type washing machine in accordance with a first preferred embodiment of the present invention includes a tub 2 of a metal inside of a cabinet(not shown) for storage of water, a drum 3 inside of the tub 2, a shaft 4 connected to the drum 3 for transmission of a driving force from a motor

5

EP 1 094 144 B1

6

5 to the drum 3, a front bearing 6a and a rear bearing 6b respectively fitted to outer circumferences of both ends of the shaft 4, a bearing housing 7 mounted to a rear wall 200 of the tub 2 for supporting the front and rear bearings, a rotor 13 mounted to a rear end of the shaft 4 to form a motor 5 together with a stator, the stator 14 on an inner side of the rotor 13 mounted to a rear wall 200 of the tub to form the motor together with the rotor, and a connector 16 serration coupled to the shaft 4 at a rear side of the rear bearing 6b and fastened to the rotor 13 for transmission of a rotating force from the rotor to the shaft 4. The bearing housing 7 is formed of a metal, preferably aluminum alloy. There is a hub 700 formed as one unit with the bearing housing 7 at a center thereof for fitting the front and rear bearings therein, and fastening bosses 701 formed on an outer side of the hub 700 at fixed intervals along a circumference for fastening the stator 14 to the bearing housing 7 with fastening members 15d such that the bearing housing 7 looks like a tripod in overall as shown in FIG. 3. In this instance, there is a step 8a and 8b formed in an inside circumference of the hub 700 on a central portion of the bearing housing 7 at each end of the hub 700 for supporting the front bearing 6a and the rear bearing 6b so that respective bearings are not fell off, but held therein. The step 8a in the front has a form of "T" for holding a rear end of the front bearing 6a, and the step 8b in the rear has a form of "L" for holding a front end of the rear bearing 6b. And, there are positioning steps 9a and 9b at front and rear circumferences of the shaft 4 for positioning the front bearing 6a and the rear bearing 6b on the shaft 4, respectively. The shaft 4 has a fore end held in a spider 10 in the rear wall of the drum 3, an exposed portion from a rear end of the spider 10 to the front bearing 6a having a bushing 11 of brass press fit thereon for prevention of rusting, with a sealing member 12 fitted on an outer circumference thereof for prevention of ingress of water, and a rear end having the rotor 13 of a direct coupling type motor 5 mounted on a center thereof. In this instance, a crown formed stator 14 is positioned on an inner side of the rotor 13, fastened to the fastening bosses 701 on the bearing housing 7 to form the direct coupling type motor in combination with the rotor 13.

[0021] Referring now to FIGS. 4 to 6, the rotor 13, formed of a magnetic material, such as iron or iron alloy, has a rear wall, a side wall, and permanent magnets provided on the side wall. There is a magnet setting surface 130, a bent part, extended from a periphery of the rear wall 13a and formed along a circumference thereof for supporting the magnets 13c fitted to an inside surface of the sidewall 13b, reinforcing the rotor 13, serving as a back yoke that forms a magnetic flux path. And, there is a hub 132 at a center of the rear wall 13a having a through hole 131 for passing of a fastening member 15a for preventing fall off of the shaft 4 from the connector 16 fixed to the rotor. The rotor 13 is preferably formed by pressing, i.e. by pressing as a unit both with the side wall 13b having the magnet setting surface and the rear

wall 13a serving as a frame for supporting the side wall, without any separate additional fabrication process.

[0022] In general, a drum washing machine may cause a problem of temperature rise owing to a load since the drum and laundry should run fast together. Therefore, there are a plurality of cooling fins around the hub 132 of the rotor 13 as a unit with the rotor 13 in a radial direction for blowing air toward the stator 14 in rotation of the rotor 13 to cool down heat generated at the stator 14. Each of the cooling fins 133 has a length in radial direction. The cooling fin 133 is formed by lancing, to be bent at approx. 90° from the rear wall 13a to direct toward opening, to form an opening 134 which serves as a vent hole. Accordingly, formation of the cooling fin 133 and formation of the vent hole are done by one process, different from a case when the formation of the vent hole is done by punching, thereby permitting saving in material and working hours as no separate component and process for forming the cooling fin is required.

[0023] And, different from BLDC motors used in VCR (Video Cassette Recorder) and the like, since the BLDC motor employed in a washing machine runs fast under a great load, the shape of the rotor is liable to deform during rotation of the rotor, which causes a non-uniform gap between the rotor and the stator. In order to eliminate this problem, there is an embossing 135 between every adjacent cooling fins 133 for reinforcing the rotor 13 together with the foregoing setting surface 130. Moreover, there is a channel sectioned rim 13d at an end of the rotor for stiffening the end for maintaining a true circle even if the rotor 13 rotates at a high speed. And, there is a draining hole 136 in the embossing 135 for discharge of water. And, there are fastening holes 137 for fastening the connector 16 serration coupled to an outer circumference of the shaft 4 at a rear end thereof exposed at a rear of the rear bearing 6b and the positioning holes 138 for fixing a position of assembly of the connector 16, both of which are formed around the through hole 131 in the hub 132 of the rotor 13 at fixed intervals. The connector 16 is formed of a resin which has a vibration mode different from that of the body of the rotor 13 of iron or iron alloy, for attenuating a vibration occurred in rotation of the drum. The fastening hole 137 and the positioning hole 138 in the connector 16 have diameters different from each other.

[0024] Referring to FIGS. 2A-2C, 8 and 9, the connector 16 has fastening holes 162 in correspondence to the fastening holes in the hub 132 of the rotor 13 along a circumference of a periphery thereof, and positioning projections between adjacent fastening holes 162 for automatic match between the fastening holes 137 in the rotor 13 and the fastening holes 162 in the connector 16 as the positioning projections 160 are inserted into the positioning holes 138 in the connector 13. And, there is a serration 164 in an inside circumference of the hub 163 of the connector 16 matched to the serration 400 in the rear end of the shaft 4, and there are reinforcing ribs

161 on an outer side of the hub 163 of the connector 16 for reinforcing the hub 163.

[0025] Referring to FIGS. 2B, 2C, and 7, the stator 14, forming the motor 5 together with the rotor 13, includes a plurality of magnetic cores 145 each formed by stacking magnetic laminations each having a salient pole projected outward in a radial direction and a rib 143 projected inward in a radial direction, both of which are formed as one unit, frames 140 of insulating material for covering top and bottom surfaces of a magnetic core assembly of the magnetic cores 145, and coils 142 wound around the salient poles of the magnetic cores.

[0026] There are tub brackets 17 welded to an outer circumference of the tub 2 for fixing the bearing housing 7 at a rear portion of the tub, and fastening holes 170 at rear ends of the tub brackets 17 for passing of fastening members 15d fastened to the fastening holes 702 formed in an end portion of the bearing housing 7 in a radial direction.

[0027] The operation of the aforementioned structure of a driving unit in a drum type washing machine in accordance with a first preferred embodiment of the present invention will be explained.

[0028] Upon rotation of the rotor 13 as a current flows to the coils 142 of the stator 14 in a sequence under the control of a motor driving controller in a panel part(not shown), the shaft 4 serration coupled to the connector 16 which is in turn connected to the rotor is rotated, to rotate the drum 3 as a power is transmitted to the drum through the shaft 4.

[0029] The assembly process of the first embodiment structure of a driving unit in a drum type washing machine of the present invention will be explained.

[0030] First, the drum 3 is placed inside of the tub 2. In this instance, the bushing 11 is press fit on an exposed portion of the shaft from rear of the spider 10 to the front bearing 6a for prevention of rusting of the shaft, and the sealing member 12 is fitted on the bushing 11 for prevention of ingress of water toward the bearing. Then, the front bearing 6a is inserted on the shaft 4 in a state the drum 3 is placed inside of the tub 2. After insertion of the front bearing 6a, the bearing housing 7 is fixed to the rear of the tub as the fastening member 15d passes through the fastening hole 170 in the tub bracket 17 welded to outer circumference of the tub 2 and fastened to the fastening hole 702 in the bearing housing 7. After completion of mounting of the bearing housing 7 to the tub 2, the rear bearing 6b is fitted to the rear end of the shaft 4. In this instance, the rear bearing 6b is held at the step 9b in rear portion of the shaft 4 and the step 8b inside of the bearing housing 7 at an end thereof. In this condition, after the fastening holes 143a in the fastening ribs 143 of the stator are aligned with the fastening bosses 701 on the bearing housing 7 on the outer side of the hub 700 at fixed intervals along a circumference, the stator is fastened to the fastening bosses 701 with the fastening members 15c, to fix the stator 14 to the bearing housing 7, firmly. Then, after an assembly of the rotor

13 and the connector 16, which assembly is done separately, is inserted onto the rear end of the shaft 4, the fastening member 15a is fastened, to prevent the connector 16 from falling off the shaft by a fastening force of the fastening member 15a.

[0031] The assembly process of the rotor 13 and the connector 16 will be explained.

[0032] First, the positioning holes 138 in the rotor 13 and the positioning projections 160 on the connector 16 are aligned, and the positioning projections 160 on the connector 16 are inserted into the positioning holes 138 in the rotor 13. In this temporary assembly when the positioning projections 160 on the connector 16 are merely inserted into the positioning holes 138 in the rotor 13, the fastening holes 137 in the rotor 13 and the fastening holes 162 in the connector 16 are aligned, under which condition, the fastening members 15b are fastened through the fastening holes 137 and 162, to assemble the rotor 13 and the connector 16 together.

[0033] The operation of the structure of a driving unit in a drum type washing machine of the first preferred embodiment of the present invention assembled thus will be explained.

[0034] The bearing housing 7 of a metal, such as aluminum alloy, is applicable to the drum type washing machine which has a drying cycle since the bearing housing 7 shows no thermal deformation even at a high temperature. The "I" formed step 8a in the front, and the "L" formed step 8b in the rear of the inside circumference of the bearing housing 7 hold a rear end of the front bearing 6a and a front end of the rear bearing 6b fitted on outer circumferences of the shaft 4 at both ends thereof, respectively. The positioning steps 9a and 9b in outer circumferences of a front portion and a rear portion of the shaft 4 permit to fix positions of the front bearing 6a and the rear bearing 6b with respect to the shaft 4. In the meantime, the front end of the shaft 4 is fixed in the spider 10 mounted to a rear wall of the drum 3, the exposed portion of the shaft from rear of the spider 10 to the front bearing 6a has the bushing 11 press fit thereon for prevention of rusting of the shaft, and the sealing member 12 is fitted on the bushing 11 for prevention of ingress of water toward the bearing. The fastening bosses 701 on the bearing housing 7 on the outer side of the hub 700 at fixed intervals along a circumference permits the stator 14 to be fastened to the fastening bosses 701 with the fastening members 15c, to fix the stator 14 to the bearing housing 7, firmly. And, the rotor 13 of the direct coupling type motor 5 is fixed to the rear end of the shaft 4, and the bent part having the magnet setting surface 30 formed along a circumference of the sidewall 13b extended forward from a periphery of the rear wall 13a of the rotor 13 supports the magnets 13c attached to the rotor 13, thereby permitting an easy fabrication of the rotor. The through hole 131 in the hub 132 at a center of the rear wall 13a of the rotor 13 permits to fasten the fastening members 15a, such as bolts, to the rear end of the shaft for prevention of

falling of the shaft 4 off the rotor 13 and the connector 16 coupled to the rotor 13, and the plurality of cooling fins 133 formed around the hub 132 of the rotor 13 in a radial direction each with a length blow air toward the stator 14 when the rotor 13 is rotated, thereby cooling down the heat generated at the stator 14. The cooling fin 133 formed to direct the open side of the rotor 13 by lancing forms the through hole 134 which serves as a vent hole. The body of the rotor 13 formed of iron or iron alloy by pressing reduces a fabrication time period very much, to improve a productivity of the rotor. The embossing 135 between adjacent cooling fins 133 on the rear wall 13a of the rotor improve an overall strength of the rotor 13, and the draining hole 136 in the embossing 135 permits to discharge water. The fastening holes 137 for fastening the connector and the positioning holes 138 for fixing a position of assembly of the connector 16, both of which are formed around the through hole 131 in the hub 132 of the rotor 13 permits to assemble the connector 16, serration coupled to the rear end of the shaft 4 exposed in rear of the rear bearing 6b, and the rotor 13 with easy. Once the positioning projections on the connector 16 are aligned with the positioning holes 138 in the rotor 13, the fastening holes 137 and 162 in both of the rotor 13 and the connector 16 are aligned automatically, through which the fastening members 15b are fastened, to assemble the connector 16 and the rotor 13 with ease. In this instance, the connector 16 of a resin injection molding has a vibration mode different from that of the rotor 13 of iron or iron alloy, to attenuate the vibration from the rotor 13 to the shaft 4. The serration 164 on an inside circumference of the hub 163 of the connector 16 is fitted to the serration 400 on the rear end of the shaft 4, to transmit a rotation force from the rotor 13 to the shaft 4 as it is. There is a cylindrical outer rib 165 spaced from the outer circumference of the hub 163, an end of which is brought into close contact with the rotor for being held, firmly. A space formed between the hub 163 and the outer rib 165 cuts off transmission of vibration from the shaft to the rotor or vice versa. The reinforcing ribs 161 in the space connecting the hub 163 and the outer ribs 167 permits an overall strength of the connector 16 adequate.

[0035] A structure of a driving unit in a drum type washing machine in accordance with a second preferred embodiment of the present invention will be explained with reference to FIGS. 10 and 11. Second embodiment components identical to those of the first embodiment will be given the same reference symbols, and explanations of which will be omitted. The second embodiment structure further includes an arc formed baffle 703 on an upper portion of outer side of the rotor 13 mounted to the bearing housing 7 for prevention of ingress of water into motor 5, which water is dropped from a water supply valve 25 when the water supply valve 25 is out of order. The arc formed baffle 703 has a length connecting both ends of the arc greater than the diam-

eter of the rotor 13. Provided that the baffle 703 is formed to have a length enough to project an end thereof beyond a rear of the sidewall 13b of the rotor, though it does not matter that an angle θ between the rear wall 200 of the tub and a top surface of the baffle 703 is 90° or greater than 90° , it is preferable that the angle θ is smaller than 90° .

[0036] The operation of the aforementioned structure machine in accordance with a second preferred embodiment of the present invention will be explained.

[0037] In the related art, since the motor 5a is mounted to a lower portion of the tub 2, even though leakage of water from the water supply valve 25 causes no ingress of water into the motor even if the leaked water drops from the water supply valve 25 owing to the water supply valve 25 being out of order, in the structure of a driving unit in a drum type washing machine of the present invention, since the motor 5 is mounted to rear of the tub 2, the water dropped when the water supply valve 25 is out of order flows toward the motor 5, which should be prevented. In order to prevent this in the present invention, the arc formed baffle 703 is provided to surround the rotor from an outer upper side of the rotor in the bearing housing 7 for prevention of the water flow toward the motor 5, thereby securing a reliability of the motor without shifting a position of the water supply valve 25. It is preferable that the angle θ between the rear wall 200 of the tub 2 and the top surface of the baffle 703 is less than 90° so that the water flows on the rear wall, but the angle θ does not matters as far as a length of the baffle 703 from a fixed end to a free end is enough to cover the sidewall 13b of the rotor.

[0038] A structure of a driving unit in a drum type washing machine in accordance with a third preferred embodiment of the present invention will be explained with reference to FIG. 12. Third embodiment components identical to those of first or second embodiment will be given the same reference symbols, and explanations of which will be omitted.

[0039] Referring to FIG. 12, the structure of a driving unit in a drum type washing machine in accordance with a third preferred embodiment of the present invention further includes a self aligning type rib 705 having a slope 705a at one side thereof formed in the bearing housing 7 along a circumference on an outer side of the fastening boss 701, and a self aligning type rib 144 having a slope 144a in correspondence to the slope 705a in the self aligning type rib 705 on an inner side of a frame 140 of the stator 14.

[0040] The operation of the aforementioned structure in accordance with a third preferred embodiment of the present invention will be explained.

[0041] The self aligning type rib 705 having a slope 705a at one side thereof formed in the bearing housing 7 along a circumference on an outer side of the fastening boss 701, and the self aligning type rib 144 having a slope 144a in correspondence to the slope 705a in the self aligning type rib 705 on an inner side of a frame 140

11

EP 1 094 144 B1

12

of the stator 14 permits self alignment of the stator 14 with the hub 700 on the bearing housing 7 on an exact concentric circles in assembly, thereby permitting an easy assembly of the stator to the bearing housing.

[0042] A structure of a driving unit in a drum type washing machine in accordance with a fourth preferred embodiment of the present invention will be explained with reference to FIG. 13.

[0043] Referring to FIG. 13, the structure of a driving unit in a drum type washing machine in accordance with a fourth preferred embodiment of the present invention includes a tub 2 having a hub 201 projected forward from a central portion of a rear wall 200 inside of a cabinet (not shown) for storage of water, a drum 3 inside of the tub 2, a shaft 4 connected to the drum 3 for transmission of a driving force from a motor 5 to the drum 3, a front bearing 6a and a rear bearing 6b respectively fitted to outer circumferences of both ends of the shaft 4, a supporting bracket 8 fastened to one side of the hub 201 of the tub 2 by fastening members 15d passed through fastening holes 801 having a step 800 for supporting the rear bearing 6b and fastening holes 802 for mounting the stator thereon, a connector 16 serration coupled to a rear end of the shaft 4, a rotor 13 of the motor 5 together with the stator coupled to the connector 16, and the stator 14 of the motor together with the rotor 13 fastened to the rear wall 200 of the tub on an inner side of the rotor 13. The bracket 8 is preferably formed of a metal, such as an aluminum alloy. There is a step 202 at an inside end of the hub 201 of the tub 2 for holding a front end of the front bearing 6a fitted on an outer circumference of the shaft 4 at a front end thereof. And, the step 800 at an inside end of the supporting bracket 8 holds a front end of the rear bearing 6b fitted on an outer circumference of the shaft 4 at a rear end thereof. The shaft 4 inside of the supporting bracket 8 for transmission of a driving force from the motor 5 has positioning steps 9a and 9b in an outer circumferences of the front end and the rear end thereof for fixing positions of the front bearing 6a and the rear bearing 6b with respect to the shaft 4, a front end fixed to a spider 10 provided to the rear wall of the drum 3, an exposed portion from a rear end of the spider 10 to the front bearing 6a having a bushing 11 of brass press fit thereon for prevention of rusting, with a sealing member 12 fitted on an outer circumference thereof for prevention of ingress of water, and a rear end having a fastening member 15a fastened to a center for preventing the connector for connection with the rotor 13 of the direct coupling type motor 5 from falling off. The stator 14 of the direct coupling type motor is positioned on the inner side of the rotor 13 and fastened to the fastening holes 801 in the supporting bracket 8. And, there is an arc formed baffle 210 on an upper portion of the rear wall of the tub 2 for prevention of water flow into the motor 5 dropped from the water supply valve when the water supply valve 25 is out of order. The arc formed baffle 210 has a length connecting both ends of the baffle greater than the diameter of the rotor.

Provided that the baffle 210 is formed to have a length enough to project an end thereof beyond the rear of the sidewall 13b of the rotor, though it does not matter that an angle θ between the rear wall 200 of the tub and a top surface of the baffle 210 is 90° or greater than 90° , it is preferable that the angle θ is smaller than 90° .

[0044] Since the rotor, stator, connector, and the baffle have structures identical to the first and second embodiments, explanations of which will be omitted.

[0045] The operation of the structure of a driving unit in a drum type washing machine in accordance with a fourth preferred embodiment of the present invention will be explained.

[0046] When the rotor 13 is rotated as a current flows to the coils 142 of the stator 14 in a sequence under the control of a motor driving controller on a panel part(not shown), the shaft 4, serration coupled to the connector 16 which is in turn connected to the rotor, is rotated, to rotate the drum 3 as a power is transmitted to the drum through the shaft 4.

[0047] The assembly process of the fourth embodiment structure of a driving unit in a drum type washing machine of the present invention will be explained.

[0048] First, the front bearing 6a is inserted onto the shaft 4 in a condition the drum 3 having the shaft 4 fixed to the spider 10 at a rear of the drum 3 is assembled inside of the tub 1. According to this, the front bearing 6a inserted onto the outer circumference of the shaft 4 is fixed at the front bearing 6a is held both at the step 9a in a front portion of the shaft 4 and the step 202 in the hub 200 of the tub 2. Then, under a condition that the fastening holes 203 for fastening the supporting bracket formed in the hub 201 of the tub 2 and the fastening holes 801 in the supporting bracket 8 are aligned, the fastening members 15d are fastened, to fix the supporting bracket 8 to the hub 201 of the tub 2. After assembly of the supporting bracket 8 to the tub 2, the rear bearing 6b is inserted onto the shaft 4 through the rear end of the shaft 4 until the rear bearing 6b is held both at the step 9b in a rear portion of the shaft 4 and the step 800 in an inside end of the supporting bracket 8. Then, the fastening holes 802 in the periphery of the supporting bracket 8 and the fastening holes 143a in the fastening rib 143 of the stator 14 are aligned, and fastened with the fastening members 15c. Under this condition, an assembly of the rotor 13 and the connector 16 are inserted into the rear end of the shaft 4, and the fastening member 15a is screwed into the rear end of the shaft, for preventing the connector 16 from falling off the shaft by a fastening force of the fastening member 15a, thereby fixing the stator 14 to the supporting bracket 8.

[0049] The operation of the structure of a driving unit in a drum type washing machine in accordance with a fourth preferred embodiment of the present invention will be explained.

[0050] In the fourth embodiment structure of a driving unit in a drum type washing machine of the present invention, since the supporting bracket 8 is formed of a

13

EP 1 094 144 B1

14

metal, such as aluminum alloy, which is involved in no thermal deformation even at a high temperature, the supporting bracket 8 is applicable to the drum type washing machine which has a drying cycle. That is, the step 800 in an inside end of the supporting bracket 8 in the fourth preferred embodiment of the present invention permits to support the front end of the rear bearing 6b. And, the positioning steps 9a and 9b in outer circumferences of front and rear portions of the shaft 4 disposed inside of the supporting bracket 8 for transmission of a driving force from the motor 5 to the drum 3 permit easy positioning of the front and rear bearings 6a and 6b with respect to the shaft 4. The front end of the shaft 4 is fixed to the spider 10 in the rear wall of the drum 3, and a portion of the shaft 4 from an end of the spider 10 to the front bearing 6a has a bushing 11 of brass press fit thereon, for prevention of rusting of the shaft 4. And, the sealing member 12 on an outer circumference of the bushing 11 prevents ingress of water into the bearing. The fastening holes 802 in the periphery of the supporting bracket 8 at fixed intervals along a circumference permit the fastening members 15c passed through the fastening holes 143a in the fastening ribs 143 on the stator 14 to pass through the fastening holes 802 in the supporting bracket, thereby permitting the stator 14 fixed to the supporting bracket 8, firmly. As the serration 164 on the inside circumference of the hub 201 of the connector 16 is fitted to the serration 400 on the rear end of the shaft 4, a rotation force can be transmitted from the rotor 13 to the shaft 4 through the connector 16 as it is. Since the supporting bracket 8 is fastened to the hub 201 projected forward from a central portion of the rear wall 200 of the tub in a face to face contact, and the stator 14 is fixed to the supporting bracket 8, a distance from the rear wall 200 of the tub to the stator 14 is very close, which permits to minimize a distance from the rear wall 200 of the tub to the rear wall 13a of the rotor, that permits to provide a compact product.

[0051] As has been explained, the structure of the present invention has the following advantages.

[0052] The first to third embodiment structure of a driving unit in a drum type washing machine can reduce noise, trouble caused by being out of order, and power loss as it is of a motor direct coupling type.

[0053] The first to third embodiment structure can be applied to a product with a drying function as the drum type washing machine of the present invention has a bearing housing formed of a metal.

[0054] The first to third embodiment structure can improve the productivity because the rotor of iron or iron alloy in the drum type washing machine of the present invention is fabricated by pressing, which has a good formability and a short fabrication time period.

[0055] And, the first to third embodiment structure can improve workability in fitting magnets as the rotor has a magnet setting surface, and can prevent over heating of the motor as the rotor has draining holes, cooling fins and vent holes to improve a reliability and a lifetime of

the motor.

[0056] And, the second embodiment structure of a driving unit in a drum type washing machine can prevent ingress of water dropped from the water supply valve 25 into the motor by means of the arc formed baffle on an upper portion of the bearing housing, thereby assuring a motor reliability.

[0057] The third embodiment structure of a driving unit in a drum type washing machine permits assembly of the stator with ease when the stator is mounted to the rear of the bearing housing owing to a self alignment action of the ribs.

[0058] The fourth embodiment structure of a driving unit in a drum type washing machine can also reduce noise, trouble from being out of order, and a power loss as it is of the motor direct coupling type.

[0059] And, the fourth embodiment structure can be applied to a product with a dry function as the supporting bracket of a metal shows no thermal deformation.

[0060] The fourth embodiment structure of a driving unit in a drum type washing machine can prevent ingress of water dropped from the water supply valve into the motor 5 by means of the arc formed baffle provided at a rear of the tub, thereby assuring a reliability of the motor.

[0061] Thus, since the drum type washing machine of the present invention can improve the structure of a driving unit, to permit direct transmission of a driving force from the motor to the drum directly, noise and trouble as well as a power loss can be reduced, to improve a productivity of the rotor and the product.

Claims

1. A drum type washing machine comprising:

a tub (2) for storing washing water,
a drum (3) of a metal rotatably mounted inside of the tub (2) disposed horizontal to the ground, or with an angle to the ground for accommodating laundry therein,
a shaft (4) connected to the drum (3) mounted inside of the tub (2) through the tub (2) for transmission of a driving force of the motor (5) to the drum (3),
bearings (6a) and (6b) fitted onto outer circumferences of both end portions of the shaft (4) for supporting the shaft (4),
a bearing housing (7) having stator fastening bosses (701) at fixed intervals along a circumference of a central portion thereof for supporting the bearings (6a) and (6b),
a stator (14) having a plurality of magnetic cores (145) each formed by stacking magnetic laminations each having a salient pole (141) projected outward in a radial direction and a rib (143) projected inward in a radial direction, both

15

EP 1 094 144 B1

16

of which are formed as one unit, frames (140) of insulating material for covering top and bottom surfaces of a magnetic core assembly of the magnetic cores (145), and coils (142) each wound around each of the salient poles (141) of the magnetic cores (145),
 a cup formed rotor (13) having a rotor body of magnetic material with a sidewall (13b) serving as a back yoke that forms a magnetic flux path and a rear wall (13a) formed as a unit with the sidewall (13b), and permanent magnets (13c) fitted to the sidewall (13b), and
 a connector (16) connecting the rotor (13) and the shaft (4),

characterized in that the sidewall (13b) comprises a "L" formed bent portion having a setting surface (130) to which the permanent magnets (13c) are fitted, and the rotor (13) includes cooling fins (133) each formed by cutting the rear wall (13a) in a "C" form, and folding in a stator direction for cooling the stator (14), and the rotor (13) further includes openings (134) each formed by the cutting of the rear wall (13a) and acting as vent holes for flow of air.

2. The drum type washing machine as claimed in claim 1, **characterized in that** the connector (16) connecting the rotor (13) and the shaft (4) for rotating the drum (3) formed of a resin different from the material of the rotor (13) for reducing vibration.
3. The drum type washing machine as claimed in claim 1, **characterized in that** the connector (16) includes
 a cylindrical hub (163) projected from a central portion for connection with the shaft (4),
 a cylindrical outer rib spaced from an outer circumference of the hub (163) to provide a space (166) for attenuating transmission of vibration between the rotor (13) and the shaft (4), and
 reinforcing ribs (161) between the hub (163) and the outer rib to connect the hub (163) and the outer rib across the space (166).
4. The drum type washing machine as claimed in claim 3, **characterized in that** the connector (16) further includes
 a serration (164) on an inside of the cylindrical hub (163) for coupling to the shaft (4), and
 positioning projections (160) on one side for positioning the connector (16) with respect to the rotor (13) before the connector (16) is fastened to the rotor (13) with bolts.
5. The drum type washing machine as claimed in claim 1, **characterized in that** the rotor (13) further includes

an embossing (135) between adjacent cooling fins (133) on the rear wall (13a) of the rotor (13) for reinforcement of the rotor (13).

- 5 6. The drum type washing machine as claimed in claim 5, **characterized in that** the embossing (135) provided for reinforcement of the rotor (13) includes a drain hole (136) for draining water.
- 10 7. The drum type washing machine as claimed in claim 1, **characterized in that** the cup formed rotor (13) includes a reinforced rim (13d) for maintaining a true circle when the rotor (13) is rotated at a high speed.

15

Patentansprüche

1. Trommelwaschmaschine mit:

20

einem Bottich (2) zum Speichern von Waschwasser,
 einer Trommel (3) aus Metall, die im Inneren des Bottichs (2) drehbar montiert und horizontal zum Boden oder mit einem Winkel zum Boden zur Aufnahme von Wäsche in ihr angeordnet ist,
 einer Welle (4), die mit der im Inneren des Bottichs (2) montierten Trommel (3), durch den Bottich (2) hindurch, zur Übertragung einer Antriebskraft des Motors (5) auf die Trommel (3) verbunden ist,
 Lagern (6a) und (6b), die auf Außenumfängen beider Endabschnitte der Welle (4) zur Lagerung der Welle (4) sitzen,
 einem Lagergehäuse (7) mit Stator-Befestigungsvorsprüngen (701) in festen Abständen entlang einem Umfang seines Mittelabschnitts zum Tragen der Lager (6a) und (6b),
 einem Stator (14) mit einer Vielzahl von Magnetkernen (145), deren jeder durch eine Schichtanordnung magnetischer Schichten gebildet ist, welche jeweils einen in radialer Richtung nach außen überstehenden, ausgeprägten Pol (141) und eine in radialer Richtung nach innen ragende Rippe (143) aufweisen, die beide als eine Einheit geformt sind, ferner mit Rahmen (140) aus Isoliermaterial zum Bedecken der Ober- und Unterseite einer Magnetkernanordnung der Magnetkerne (145), und mit Spulen (142), deren jede jeweils um die ausgeprägten Pole (141) der Magnetkerne (145) gewickelt ist,
 einem becherförmigen Rotor (13), der einen Rotorkörper aus magnetischem Material mit einer als Rückseitenjoch dienenden Seitenwand (13b), die einen magnetischen Kraftlinienweg bildet, und einer Rückwand (13a), die als eine

25

30

35

40

45

50

55

17

EP 1 094 144 B1

18

Einheit mit der Seitenwand (13b) ausgebildet ist, sowie Permanentmagnete (13c) aufweist, die an der Seitenwand (13b) sitzen, und einem Anschluß (16), der den Rotor (13) und die Welle (4) verbindet,

dadurch gekennzeichnet, daß die Seitenwand (13b) einen "L"-förmigen, gebogenen Abschnitt mit einer Sitzfläche (130) umfaßt, an der die Permanentmagnete (13c) sitzen, und daß der Rotor (13) Kühllamellen (133), deren jede durch "C"-förmiges Ausschneiden der Rückwand (13a) und Falten in Statorrichtung zum Kühlen des Stators (14) gebildet ist, aufweist, wobei der Rotor (13) ferner mit Öffnungen (134) versehen ist, deren jede durch das Ausschneiden der Rückwand (13a) gebildet ist und als Entlüftungsloch für einen Luftstrom dient.

2. Trommelwaschmaschine nach Anspruch 1, **dadurch gekennzeichnet, daß** der Anschluß (16), der den Rotor (13) und die Welle (4) zum Drehen der Trommel (3) verbindet, aus einem Harz gebildet ist, das sich von dem Material des Rotors (13) unterscheidet, um Vibrationen zu dämpfen.

3. Trommelwaschmaschine nach Anspruch 1, **dadurch gekennzeichnet, daß** der Anschluß (16) folgendes umfaßt:

eine zylindrische Nabe (163), die von einem Mittelabschnitt vorspringt, zum Anschluß an die Welle (4),

eine zylindrische äußere Rippe, die von einem Außenumfang der Nabe (163) so beabstandet ist, daß sie einen Raum (166) zum Dämpfen der Schwingungsübertragung zwischen dem Rotor (13) und der Welle (4) bildet, und Verstärkungsrippen (161) zwischen der Nabe (163) und der äußeren Rippe, um die Nabe (163) und die äußere Rippe durch den Raum (166) zu verbinden.

4. Trommelwaschmaschine nach Anspruch 3, **dadurch gekennzeichnet, daß** der Anschluß (16) ferner folgendes aufweist:

eine Kerbverzahnung (164) an einer Innenseite der zylindrischen Nabe (163) zum Ankoppeln an die Welle (4) und Positioniervorsprünge (160) auf einer Seite zum Positionieren des Anschlusses (16) relativ zum Rotor (13), bevor der Anschluß (16) mit Bolzen am Rotor (13) befestigt wird.

5. Trommelwaschmaschine nach Anspruch 1, **dadurch gekennzeichnet, daß** der Rotor (13) zudem noch eine Erhebung (135) zwischen benachbarten Kühlrippen (133) an der Rückwand (13a) des Ro-

tors (13) zur Verstärkung des Rotors (13) umfaßt.

6. Trommelwaschmaschine nach Anspruch 5, **dadurch gekennzeichnet, daß** die zur Verstärkung des Rotors (13) vorgesehene Erhebung (135) ein Ablaufloch (136) zum Ablauf von Wasser umfaßt.

7. Trommelwaschmaschine nach Anspruch 1, **dadurch gekennzeichnet, daß** der becherförmige Rotor (13) eine verstärkte Außenzone (13d) zum Beibehalten eines echten Kreises umfaßt, wenn der Rotor (13) bei einer hohen Geschwindigkeit gedreht wird.

Revendications

1. Machine à laver du type à tambour, comprenant :

une cuve (2) pour emmagasiner de l'eau de lavage,

un tambour (3) en métal monté de façon à pouvoir tourner à l'intérieur de la cuve (2) et disposé horizontalement par rapport au sol ou avec un certain angle par rapport au sol pour recevoir du linge,

un arbre (4) relié, à travers la cuve (2), au tambour (3) monté à l'intérieur de ladite cuve (2), afin de transmettre une force d'entraînement d'un moteur (5) au tambour (3),

des paliers (6a) et (6b) rapportés sur les circonférences extérieures des deux parties d'extrémité de l'arbre (4) pour supporter ce dernier,

un logement de palier (7) pour supporter les paliers (6a) et (6b), ayant des bossages de fixation de stator (701) à intervalles fixes le long d'une circonférence de sa partie centrale,

un stator (14) ayant une pluralité de noyaux magnétiques (145) formés chacun en empilant des tôles magnétiques ayant chacune un pôle saillant (141) qui fait saillie vers l'extérieur dans une direction radiale et

une saillie (143) qui s'étend vers l'intérieur dans une direction radiale, pôle et saillie qui sont formés tous les deux d'une seule pièce, des cadres (140) en matière isolante recouvrant les surfaces inférieure et

supérieure de l'ensemble des noyaux magnétiques (145), et des bobines (142) enroulées chacune autour de chacun des pôles saillants (141) des noyaux magnétiques (145),

19

EP 1 094 144 B1

20

un rotor (13) en forme de cuvette, ayant un corps en une matière magnétique, avec une paroi latérale (13b) servant de culasse qui établit un trajet de flux magnétique, et une paroi arrière (13a) formée d'une seule pièce avec la paroi latérale (13b), et des aimants permanents (13c) rapportés sur la paroi latérale (13b), et

un raccord (16) reliant le rotor (13) à l'arbre (4),

caractérisée en ce que la paroi latérale (13b) comporte une partie coudée en forme de « L » ayant une surface de calage (130) sur laquelle les aimants permanents (13c) sont calés, et le rotor (13) comporte des ailettes de refroidissement formées chacune par le découpage de la paroi arrière (13a) selon une découpe en forme de « C » et par pliage en direction du stator, pour refroidir le stator (14), et le rotor (13) comporte en outre des ouvertures (134) formées chacune par le découpage de la paroi arrière (13a) et agissant comme des trous d'évent pour l'écoulement de l'air.


2. Machine à laver du type à tambour selon la revendication 1, **caractérisée en ce que** le raccord (16) reliant le rotor (13) à l'arbre (4) pour faire tourner le tambour (3) est formé d'une résine différente de la matière du rotor (13) afin de réduire les vibrations.
3. Machine à laver du type à tambour selon la revendication 1, **caractérisée en ce que** le raccord (16) comporte une moyeu cylindrique (163) qui s'étend à partir d'une partie centrale pour la liaison avec l'arbre (4), une nervure cylindrique extérieure espacée de la circonférence extérieure du moyeu (163) afin de ménager un espace (166) destiné à atténuer la transmission des vibrations entre le rotor (13) et l'arbre (4), et des nervures de renfort (161) entre le moyeu (163) et la nervure extérieure, pour relier le moyeu (163) et la nervure extérieure à travers l'espace (166).
4. Machine à laver du type à tambour selon la revendication 3, **caractérisée en ce que** le raccord (16) comprend en outre des canelures (164) sur une surface intérieure du moyeu cylindrique (163) pour un accouplement à l'arbre (4), et des saillies de positionnement (160) sur un côté pour positionner le raccord (16) par rapport au rotor (13) avant que le raccord (16) soit fixé au rotor (13) par des boulons.
5. Machine à laver du type à tambour selon la revendication 1, **caractérisée en ce que** le rotor (13) comprend en outre un bosselage (135) entre des ailettes adjacentes de

refroidissement (133) sur la paroi arrière (13a) du rotor (13), pour le renforcement du rotor (13).

6. Machine à laver du type à tambour selon la revendication 5, **caractérisée en ce que** le bosselage (135) prévu pour le renforcement du rotor (13) comporte un trou de drainage (136) pour drainer de l'eau.
7. Machine à laver du type à tambour selon la revendication 1, **caractérisée en ce que** le rotor (13) en forme de cuvette comporte un bord replié et renforcé (13d) pour y maintenir un cercle véritable lorsque le rotor (13) est entraîné en rotation à grande vitesse.


EP 1 094 144 B1

FIG. 1
RELATED ART




EP 1 094 144 B1

FIG. 2A




EP 1 094 144 B1

FIG. 2B




EP 1 094 144 B1

FIG. 2C




EP 1 094 144 B1

FIG. 3




EP 1 094 144 B1

FIG. 4




EP 1 094 144 B1

FIG. 5




EP 1 094 144 B1

FIG. 6




EP 1 094 144 B1

FIG. 7




EP 1 094 144 B1

FIG. 8




EP 1 094 144 B1

FIG. 9




EP 1 094 144 B1

FIG. 10




EP 1 094 144 B1

FIG. 11



EP 1 094 144 B1

FIG. 12



EP 1 094 144 B1

FIG. 13

